

Acid / Alkali Security Cupboards



Sizes Available

Floor Versions:

- 1800Hx900Wx460Dmm - 3 shelves - 14 litres capacity.
- 1800Hx1200Wx460Dmm - 3 shelves - 18 litres capacity.
- 1200Hx900Wx460Dmm - 2 shelves - 14 litres capacity.
- 1200Hx1200Wx460Dmm - 2 shelves - 16 litres capacity.
- 900Hx460Wx460Dmm - 1 shelf - 7 litres capacity.



Paint Finish

A three-stage pre-treatment and phosphate coating are applied. Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180deg, including our germ guard anti-bacterial compound. The product is powder-coated - White - BS 00.E.55



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



Delivery

All sizes are manufactured-to-order.

Acid / Alkali Security Cupboards



Cupboard Construction

General Construction:

- 1.2mm mild steel, seam-welded carcass construction.
- Full-length piano hinges.
- Adjustable spill-retaining galvanised shelves for superior spill management with a UDL of 140KG.
- Integral liquid-tight sump fitted at the bottom of the cupboard.
- The door aperture has return bends to eliminate open gaps.
- Seven-lever safe lock and an anti-pick locking mechanism.
- Delivered as a fully assembled unit.
- Warning/hazardous labels supplied.
- The integral sump has fully welded seams and is manufactured from 1.2mm mild steel.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.
- 1.2mm thick steel door with full-length welded/riveted continuous hinge, incorporating retaining rail to prevent hinge/door removal.
- Two-point espagnolette locking mechanism secures both doors into the carcass. Fitted with a 7-lever Lowe & Fletcher 2802 anti-pick safe lock.



Our live chat satisfaction rating,
based on user feedback