

CoSHH Cupboards



Sizes Available

Floor Versions:

1800Hx900Wx460Dmm - 3 shelves - 14-litre sump capacity.

1800Hx1200Wx460Dmm - 3 shelves - 18-litre sump capacity.

1200Hx900Wx460Dmm - 2 shelves - 14-litre sump capacity.

900Hx460Wx460Dmm - 1 shelf - 7-litre sump capacity.

900Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.

700Hx350Wx300Dmm - 1 shelf - 3-litre sump capacity.

700Hx900Wx460Dmm - 1 shelf - 14-litre sump capacity.



Mobile Versions:

1040Hx900Wx460Dmm - 1 shelf - no sump fitted.

840Hx900Wx460Dmm - 1 shelf - no sump fitted.



Floor Chest Versions:

610Hx1170Wx460Dmm - no shelf - 20-litre sump capacity.

510Hx610Wx340Dmm - no shelf - 7-litre sump capacity.

Wall-Mounted Version:

570Hx850Wx255Dmm - 1 shelf - no sump fitted.



Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180deg, including our germ guard anti-bacterial compound.

The product is powder-coated - Dark Grey - RAL 7024.



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).

CoSHH Cupboards



Cupboard Construction

General Construction:

- 0.7mm mild steel, pop riveted carcass construction.
- Integral liquid-tight sump fitted at the bottom of the cupboard (*except wall-mounted cupboard*).
- Door aperture has return bends to eliminate open gaps.
- Delivered as a fully assembled unit.
- Warning/hazardous labels supplied.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.
- Fitted with "no snag" 2-point locking mechanism.
- Adjustable spill-retaining galvanised shelves for superior spill management with a UDL of 50KG.

Floor Chest Construction:

- Material: 1.5mm mild steel.
- Fully welded integrated sump & angled lid to discourage article placement.
- Fully welded construction with 2 no. welded 2.5" butt hinges.
- Connected to the carcass with 4.8mm pop rivets.
- Fitted with restraint to prevent lid from falling back.
- Supplied with hasp and staple (padlock not supplied).



Our live chat satisfaction rating,
based on user feedback



Delivery Lead-Time

This is a manufactured-to-order item and will be on an extended lead-time.