

Perforated Cupboard Specification Sheet



Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>	<u>Shelves Supplied</u>
1800mm	600mm	460mm	3
1800mm	900mm	460mm	3
1800mm	1200mm	460mm	3
1800mm	900mm	610mm	3
1800mm	1200mm	610mm	3
1200mm	900mm	460mm	2
900mm	900mm	460mm	2
900mm	900mm	610mm	2
900mm	460mm	460mm	1
(Mobile Cupboard) 1040mm	900mm	460mm	2
(Mobile Cupboard) 1040mm	900mm	610mm	2

Cupboard Construction:

- 0.7mm mild steel, pop riveted carcass construction
- Rust resisting galvanised shelves
- Door aperture has return bends to eliminate open gaps
- Delivered assembled
- Reaction to Fire Classification EN 13501-1 – documents available
- 2-point locking mechanism
- Extra Shelves available with the Perforated Cupboard range

Cupboard Door Construction:

Material: 0.9mm Mild Steel


A stiffener is spot welded vertically in the centre of the door. Two 2.½” butt hinges are spot welded to the door. The door is attached to the carcass via the hinges, with 4.8mm pop rivets. The door has two-point locking with an all metal key locking handle. A series of square holes 20mm x 20mm are punched in the door to create the perforation.

Paint Finish:

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound
- Carcass powder coated with a Light Grey – **RAL 7035**

Door colour:

Red	RAL 3003
Green	RAL 6024
Light Blue	RAL 5012
Dark Blue	RAL 5017
Light Grey	RAL 7035
Yellow	RAL 1018



Equipment Cleaning & Maintenance instructions:

- Clean paint work periodically with warm soapy water
- Oil hinges and lock sparingly as required with a light oil (3in1 or similar)